



DEVIlink™ CC

The DEVIlink™ CC (Central Controller) is the central brain in a DEVIlink™ system. It has a colour “touch” screen which is also WiFi enabled to allow control via the DEVIlink™ App (iOS or Android) of your heating when you are away from the home/building.

The DEVIlink™ CC will communicate wirelessly with up to 30 individual rooms and up to 50 devices.

The DEVIlink™ CC software is automatically updated from the internet.

A context sensitive Help Guide gives additional information on every screen image.

Benefits:

- Central control of the entire house
- Minimize energy consumption
- Vacation mode
- Controlling of ON/OFF devices
- Weekly heating schedule
- Remote control via smart device app

Standard compliance:

- The DEVIlink™ CC is in compliance with EN 60730 and EN 300 220-2.

Certificates:



Type	Value
Operation voltage	15 V DC ±10%
Standby power consumption	Max. 2 W
Screen	3.5" TFT colour w. touch
Ambient temperature	-10 to +40 °C
Storage temperature	-20 to +65 °C
Ball pressure test temperature	75 °C
Pollution degree	2 (domestic use)
Transmission frequency	868.42 MHz
Transmission range	Up to 30 m
Wi-Fi	802.11b, g or n (2.4 GHz)
Max. repeaters in a chain	3
Transmission power	Max. 1 mW
Software class	A
IP class	21
Dimensions	125 x 107 x 25 mm
Weight	179 g

Types

Code No.	Name	Description
01-140F1135	DEVIlink™ CC - WiFi	Wireless Central Controller for DEVIlink system. <i>Wi-Fi control by smart device app (allowing worldwide remote control)</i>

System Units

Code No.	Name	Description
01-140F1137	DEVIlink™ FT	Flush Mounted Floor sensing thermostat <i>(Supplied for fitting to a Euro Flush Box)</i>
01-140F1136	DEVIlink™ RS	Wireless Room Temperature Sensor thermostat (Dry Cell battery powered)
01-140F1138	DEVIlink™ RU	Wireless Repeater unit <i>(for larger installations).</i>




DEVIlink™ CC

The total number of wireless units within a DEVIlink™ system may not exceed 50 - 1x CC and 49x units (Floor thermostats and/or Room Air Temp sensors).

The number of each type of unit may not exceed -

DEVIlink™ CC (Central Controller)	1 unit
DEVIlink™ FT (Floor thermostat)	30 units
DEVIlink™ RS (Room Sensor)	30 units
DEVIlink™ RU (Repeater unit)	4 units

Appearance of the mounting plate supplied with the DEVIlink™ CC.

DEVIlink™ CC details		
	Operating Voltage	230 VAC 50Hz
	Recommended Protection Fuse	Max. 16 A
	Output Voltage	15 VDC ±10%
	Standby Power Consumption	Max. 0.15 W
	Max. Load	10 W
	Cable Specification	Recommend 2x 1.5mm ² , max. 2x 2.5mm ²