




DEVIlink™ RS

The DEVIlink™ RS (Room Sensor) is a battery operated device for measuring room temperature. It is only to be mounted directly on the wall.

When using the DEVIlink™ RS as heating regulation it must be installed together with a DEVIlink™ PR, DEVIlink™ HR or DEVIlink™ FT to secure the required comfort and convenience.

Be aware that all DEVIlink™ RS in the same room must have the same configuration.

Benefits:	Type	Value
<ul style="list-style-type: none"> Heating regulation Wireless connected to DEVIlink™ CC Actually temperature view Adjustable Daily overview Weekly schedule Minimize energy consumption <p>Standard compliance:</p> <ul style="list-style-type: none"> The DEVIlink™ RS is in compliance with EN 60730 and EN 300 220-2. <p>Certificates:</p> 	Battery	Alkaline 2 × AA, 1,5 V
	Battery Lifetime	Up to 4-5 years
	Backlight	Green LED
	Ambient temperature	0° to +40°C
	Battery monitoring	The sensor has a built-in monitoring circuit, which will detect low or critical battery level.
	Transmission frequency	868,42 MHz
	Transmission range in normal buildings	Up to 30 m
	Transmission power	Max. 1 mW
	IP class	21
	Dimension (H/W/D)	81 mm × 66 mm × 21 mm

Types

Code No.	Name	Description
01-140F1136	DEVIlink™ RS	Wireless Room Temperature Sensor thermostat (Dry Cell battery powered)