

# DEVI Connect



**DEVI Connect** Zigbee gateway and app make it easy to manage your Zigbee-enabled devices. **DEVI Connect** is designed for the end user to access the most important features from anywhere at any time. Think of the app as a remote control for your smart home, allowing you to

adjust settings and monitor devices from anywhere. The gateway acts like a translator, helping your devices communicate with the app smoothly. The gateway only needs to be plugged into the users internet router, where it will then be possible to add to the app.

## Benefits:

- Zigbee connectivity
- In app setup
- Plug and play gateway
- Remote and local control
- Power adapter included
- Multilanguage app
- Shine through indicators for power and network
- Customizable scheduling

## Standard compliance:

- EN 62368-1:2020
- EN 18031-1:2024
- EN 301489
- EN 55032
- EN 55035

## Compliance symbols:



| Type                                                | Value                                  |
|-----------------------------------------------------|----------------------------------------|
| Adapter                                             | 100 V- 240V~ 50/60 Hz , 5V 1A DC       |
| Power Consumption / Standby                         | < 5W / < 2W                            |
| Wired Communication                                 | 10/100M Ethernet Port (RJ45, LAN)      |
| Power supply                                        | 5VDC (USB-C)                           |
| Wireless communication                              | Zigbee                                 |
| Transmission range                                  | Up to 30m.                             |
| Pollution degree                                    | 2 (domestic use)                       |
| Firmware updates                                    | Supports over the air updates          |
| Storage temperature and conditions                  | -20 °C to 60 °C, 90% RH non-condensing |
| Operating temperatures and conditions               | -10 °C to 45 °C, 90% RH non-condensing |
| IP class                                            | X0                                     |
| Protection class                                    | Class III                              |
| Transmission frequency (GHz)                        | 2.405 – 2.480 GHz                      |
| Transmission Power (dBm)                            | <19 dBm                                |
| Color                                               | RAL9016 Polar white                    |
| Dimensions (H/W/D):                                 | 90mm x 90mm x 23mm                     |
| Weight, net                                         | 152 g                                  |
| Number of users who can join home (DEVIConnect App) | 20 pcs                                 |
| Number of homes in app (DEVIConnect App)            | 20 pcs                                 |
| Number of devices per DEVI Connect (gateway)        | 200 units                              |

## Types: DEVI Connect

| Item no.    | Product name        | Type                            | EAN no.       |
|-------------|---------------------|---------------------------------|---------------|
| 01-140F1166 | <b>DEVI Connect</b> | Gateway for zigbee connectivity | 5703466253199 |

## Compatible products

| Item no.    | Product name                    | Type                                                                        | EAN no.       |
|-------------|---------------------------------|-----------------------------------------------------------------------------|---------------|
| 01-140F1170 | <b>DEVIreg™ InControl</b>       | Connectable Zigbee thermostat with NTC 15 kΩ @ 25°C, 3 m sensor in box      | 5703466250419 |
| 01-140F1162 | <b>DEVIreg™ Display Connect</b> | Connectable Zigbee room thermostat with NTC 15 kΩ @ 25°C, 3 m sensor in box | 5703466250396 |

App:



[www.devi.co.nz](http://www.devi.co.nz)

DEVI Heating Systems Ltd (Head Office)  
36B Sonter Road, Wigram, Christchurch 8042  
PO Box 8582 Riccarton, Christchurch 8440  
Ph 0800 468 356 / (03) 348 0070