

# DEVIconnecto



The DEVIconnecto programme gives you different solutions for easy and safe connection of DEVI self-limiting heating cables - DEVIceguard™ (B),

DEVIpipeline™ (B), DEVIhotwatt™ (B). Using DEVIconnecto to wire up a heating circuit is fast, requiring only a knife and a diagonal cutter.

## Benefits:

- Cost savings by reduced assembly time
- Great reliability of assembly simplicity
- Safe electrical contacting by precise clamp cutting technology



Type	Value
Nominal voltage, max.	250 V~
Max. current	16 A
Ambient temperature	-25 °C to +65°C (heating cables are powered) -25 °C to +85°C (heating cables are unpowered)
IP class	IP 66

## Types

Product Code	Product name	Description
1-19808360	DEVIconnecto B-A	Connection power supply
1-19808361	DEVIconnecto B-C	Heating cable connection
1-19808362	DEVIconnecto B-E	End termination
1-19808363	DEVIconnecto B-S	Connection and end termination
1-19808364	DEVIconnecto B-T	Y-junction + end termination
1-19808365	DEVIconnecto B-TE2	Y-junction + 2 end terminations
1-19808366	DEVIconnecto B-TE3	Y-junction + 3 end terminations
1-19808367	DEVIconnecto B-X	X-junction + 2 end terminations
1-19808390	DEVIconnecto Bracket	Bracket and 6 cable ties

**ATTENTION.** DEVIconnecto may not be put in the gutters when used with DEVIceguard™ (B) . It must be installed in a dry place.

**Selection chart. DEVIconnecto for heating cables with braiding: DEVIpipeguard™ (B), DEVIhottwatt™ (B) and DEVIceguard™ (B)**

Illustration	Name	Description
	DEVIconnecto B-A	Heating cable connection with power cable 1,5 m without end terminal
	DEVIconnecto B-C	Heating cable splice/extension for connecting two heating cables
	DEVIconnecto B-E	Heating cable end terminal
	DEVIconnecto B-S	Heating cable connection with 1,5 m power cable and end terminal
	DEVIconnecto B-T	Heating cable T-branch as a T-junction for three heating cables and 1 end terminal
	DEVIconnecto B-TE2	Heating cable double connection with 1,5 m power cable and 2 end terminals
	DEVIconnecto B-TE3	Heating cable T-branch with 1,5 m power cable and 3 end terminals
	DEVIconnecto B-X	Heating cable X-branch for 4 heating cables incl. 2 end terminals
	DEVIconnecto Bracket	For installation of the DEVIconnecto connection outside the insulation 

**DEVIconnecto system installation steps**

1. Cut the heating cable straight
2. Push the heating cable in
3. Twist until closed



DEVIconnecto B-C



DEVIconnecto B-TE2



DEVIconnecto B-X