



## TH high temperature radiant terrace heater

Comfortline high temperature TH series radiant heaters are a modern and elegant black-heat technology. The heaters are of modular design and are available in 1000W, 1500W, 2000W and 3000W units.

The standard mounting bracket supplied with the heaters double as a wall bracket or a tilt bracket.

The cabinet is steel with multiple black 'Anti-cor' corrosion protective coating.

| <b>Benefits:</b><br>- Direct heat independent of the air temperature.<br>- Low energy cost.<br>- Long product life.<br><br><b>Standards Compliance</b><br>AS/NZS60335.330: 2015 A1<br><br> | Type                         | Value  |
|--|------------------------------|--------|
|  | Operating Voltage            | 230VAC |
| Power range  | 1000W - 3000W                |        |
| Lamella surface temperature  | Greater than 350 degrees C   |        |
| Lamella material   | Engineered Aluminium         |        |
| Lamella coating  | High temperature black paint |        |
| Cabinet material   | 0.8mm zincalume steel        |        |
| Corrosion protection   | Anticor coating              |        |
| Multiphase connection  | Contact Devi Heating         |        |
| Multistage connection  | Contact Devi Heating         |        |
| IP rating  | IP45                         |        |

### Dimensions.

| Model     | Length | Width | Depth | Holes C to C | Weight |
|-----------|--------|-------|-------|--------------|--------|
| 02-TH1000 | 1080mm | 140mm | 45mm  | 650mm        | 4.9kg  |
| 02-TH1500 | 1580mm | 140mm | 45mm  | 1050mm       | 6.9kg  |
| 02-TH2000 | 1080mm | 240mm | 50mm  | 650mm        | 5.8kg  |
| 02-TH3000 | 1585mm | 240mm | 50mm  | 1050mm       | 8.3kg  |

### Clearances.

| Model     | A to ceiling | B end to wall | C to flammables | D to floor <sup>NB1</sup> | L mounts |
|-----------|--------------|---------------|-----------------|---------------------------|----------|
| 02-TH1000 | 130mm        | 250mm         | 500mm           | 1800mm                    | 650mm    |
| 02-TH1500 | 130mm        | 250mm         | 500mm           | 1800mm                    | 1050mm   |
| 02-TH2000 | 170mm        | 300mm         | 1000mm          | 1800mm                    | 650mm    |
| 02-TH3000 | 170mm        | 300mm         | 1000mm          | 1800mm                    | 1050mm   |

### Features.

Black powder coated alloy body.  
 Black machine finished lamella.  
 Outdoor IP45 rated.  
 Single ended elements.  
 Single ended elements.  
 AS/NZS 60335-2.30 approved.  
 2 Year manufacturers warranty.  
 On-site maintainable.  
 Wall/ceiling tilt bracket included.  
 Can be mounted vertically or horizontally.

### Applications.

Hospitality industry.  
 Outdoor and indoor installation.  
 Cafe, restaurants and bars.  
 Patios and terraces.  
 Schools and preschools.  
 Churches.  
 Halls and offices.  
 Spa and barbeque areas.

NB1: Recommended minimum clearance.

